

### **ICNIRP Measurement Report**

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	30/01/2023	Time Survey completed:	13:26
Survey address:	Shrewsbury, Shrops	hire SY2	

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072612	14/09/2022
Probe	Agos Aria-6000 Antenna	60001117	28/11/2022
Cabling	1.7m Cable	1319	28/11/2022

<sup>&</sup>lt;sup>1</sup> https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

<sup>&</sup>lt;sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

## Mobile bands covered by this report

Frequency Band	Frequency	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

#### **Notes**

## **Survey locations**

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Map data: © Google

<sup>\*</sup> This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations.

<sup>\*\*</sup> All other frequencies between 420 MHz and 6 GHz.

# Location 1

Measurement time:	12:31
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00154
800 MHz	0.00338
900 MHz	0.00054
1400 MHz	0.00407
1800 MHz	0.00470
1900 MHz	0.00017
2100 MHz	0.00283
2300 MHz	0.00033
2600 MHz TDD	0.00029
2600 MHz FDD	0.00092
3.4 GHz	0.00224
3.8 GHz	0.00406
Others	0.06401
Total	0.08908

# Location 2

Measurement time:	12:40
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00255
800 MHz	0.00772
900 MHz	0.00053
1400 MHz	0.00387
1800 MHz	0.00589
1900 MHz	0.00018
2100 MHz	0.00779
2300 MHz	0.00034
2600 MHz TDD	0.00030
2600 MHz FDD	0.00071
3.4 GHz	0.00282
3.8 GHz	0.00421
Others	0.06629
Total	0.10320

# Location 3

Measurement time:	12:52
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00148
800 MHz	0.00293
900 MHz	0.00057
1400 MHz	0.00189
1800 MHz	0.00329
1900 MHz	0.00018
2100 MHz	0.00234
2300 MHz	0.00035
2600 MHz TDD	0.00031
2600 MHz FDD	0.00037
3.4 GHz	0.00271
3.8 GHz	0.00436
Others	0.06834
Tota	0.08912

# Location 4

Measurement time:	13:00
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00217
800 MHz	0.00633
900 MHz	0.00059
1400 MHz	0.00286
1800 MHz	0.00681
1900 MHz	0.00018
2100 MHz	0.00234
2300 MHz	0.00036
2600 MHz TDD	0.00031
2600 MHz FDD	0.00102
3.4 GHz	0.00259
3.8 GHz	0.00443
Others	0.06919
Total	0.09918

### Location 5

Measurement time:	13:09
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00116
800 MHz	0.00118
900 MHz	0.00055
1400 MHz	0.00206
1800 MHz	0.00586
1900 MHz	0.00018
2100 MHz	0.01628
2300 MHz	0.00036
2600 MHz TDD	0.00031
2600 MHz FDD	0.00062
3.4 GHz	0.00242
3.8 GHz	0.00441
Others	0.06890
Total	0.10429

### Location 6

Measurement time:	13:20
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00161
800 MHz	0.00341
900 MHz	0.00058
1400 MHz	0.00278
1800 MHz	0.00300
1900 MHz	0.00019
2100 MHz	0.00190
2300 MHz	0.00036
2600 MHz TDD	0.00032
2600 MHz FDD	0.00055
3.4 GHz	0.00254
3.8 GHz	0.00452
Others	0.07050
Total	0.09226

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.