

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	28/11/23	Time Survey completed:	15:27
Survey address:	Oldham OL10		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072599	24/01/2023
Probe	Agos Aria-6000 Antenna	60001024	30/03/2021
Cabling	1.7m Cable	1383	12/10/2023

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Mobile bands covered by this report

Frequency Band	Frequency	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

Notes

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations.

** All other frequencies between 420 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Map data: © Google

Location 1

Measurement time:	14:40
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0074
800 MHz	0.0312
900 MHz	0.0207
1400 MHz	0.0358
1800 MHz	0.0333
1900 MHz	0.0002
2100 MHz	0.0141
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0023
3.4 GHz	0.0039
3.8 GHz	0.0050
Others	0.1830
Total	0.3377

Location 2

Measurement time:	14:47
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0037
800 MHz	0.0989
900 MHz	0.0115
1400 MHz	0.0075
1800 MHz	0.0046
1900 MHz	0.0002
2100 MHz	0.0267
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0005
3.4 GHz	0.0048
3.8 GHz	0.0053
Others	0.1871
Total	0.3517

Location 3

Measurement time:	14:55
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0114
800 MHz	0.0823
900 MHz	0.0157
1400 MHz	0.0041
1800 MHz	0.0165
1900 MHz	0.0002
2100 MHz	0.0237
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0022
3.4 GHz	0.0059
3.8 GHz	0.0055
Others	0.1932
Total	0.3614

Location 4

Measurement time:	15:04
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0067
800 MHz	0.0919
900 MHz	0.0393
1400 MHz	0.0240
1800 MHz	0.0565
1900 MHz	0.0002
2100 MHz	0.0154
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0037
3.4 GHz	0.0099
3.8 GHz	0.0056
Others	0.1964
Total	0.4503

Location 5

Measurement time:	15:13
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0079
800 MHz	0.0454
900 MHz	0.0064
1400 MHz	0.0362
1800 MHz	0.0268
1900 MHz	0.0002
2100 MHz	0.0220
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0012
3.4 GHz	0.0042
3.8 GHz	0.0057
Others	0.1989
Total	0.3556

Location 6

Measurement time:	15:21
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0118
800 MHz	0.0648
900 MHz	0.0213
1400 MHz	0.0482
1800 MHz	0.0768
1900 MHz	0.0002
2100 MHz	0.0317
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0042
3.4 GHz	0.0051
3.8 GHz	0.0057
Others	0.2032
Total	0.4738

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.