

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	01/04/2025	Time Survey completed:	13:54
Survey address:	Buntingford SG9		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072607	29/10/2024
Probe	Agos Aria-6000 Antenna	ARIA-600-1023	22/01/2021
Cabling	1.7m cable	1407	23/11/2023

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.

A



Location 1

Measurement time:	12:43
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00944
174-230 MHz	0.01057
470-694 MHz	0.00846
700 MHz	0.00337
800 MHz	0.00440
900 MHz	0.00060
1400 MHz	0.00072
1800 MHz	0.00128
1900 MHz	0.00020
2100 MHz	0.00057
2300 MHz	0.00040
2600 MHz TDD	0.00036
2600 MHz FDD	0.00024
3.4 GHz	0.00196
3.8 GHz	0.00445
Others	0.13609
Total	0.18313

Location 2

Measurement time:	12:50
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00959
174-230 MHz	0.01088
470-694 MHz	0.00871
700 MHz	0.00233
800 MHz	0.00133
900 MHz	0.00061
1400 MHz	0.00087
1800 MHz	0.00217
1900 MHz	0.00020
2100 MHz	0.00065
2300 MHz	0.00042
2600 MHz TDD	0.00037
2600 MHz FDD	0.00054
3.4 GHz	0.00203
3.8 GHz	0.00462
Others	0.14101
Total	0.18634

Location 3

Measurement time:	13:02
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01013
174-230 MHz	0.01147
470-694 MHz	0.00903
700 MHz	0.00339
800 MHz	0.00442
900 MHz	0.00064
1400 MHz	0.00084
1800 MHz	0.00343
1900 MHz	0.00021
2100 MHz	0.00072
2300 MHz	0.00044
2600 MHz TDD	0.00040
2600 MHz FDD	0.00041
3.4 GHz	0.00220
3.8 GHz	0.00495
Others	0.14775
Total	0.20044

Location 4

Measurement time:	13:14
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01064
174-230 MHz	0.01200
470-694 MHz	0.00935
700 MHz	0.00520
800 MHz	0.00561
900 MHz	0.00070
1400 MHz	0.00081
1800 MHz	0.00124
1900 MHz	0.00022
2100 MHz	0.00074
2300 MHz	0.00046
2600 MHz TDD	0.00041
2600 MHz FDD	0.00033
3.4 GHz	0.00235
3.8 GHz	0.00518
Others	0.15418
Total	0.20940

Location 5

Measurement time:	13:27
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01088
174-230 MHz	0.01255
470-694 MHz	0.00976
700 MHz	0.00814
800 MHz	0.01310
900 MHz	0.00070
1400 MHz	0.00106
1800 MHz	0.00299
1900 MHz	0.00024
2100 MHz	0.00079
2300 MHz	0.00048
2600 MHz TDD	0.00043
2600 MHz FDD	0.00027
3.4 GHz	0.00241
3.8 GHz	0.00546
Others	0.16231
Total	0.23156

Location 6

Measurement time:	13:48
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01100
174-230 MHz	0.01237
470-694 MHz	0.00974
700 MHz	0.00313
800 MHz	0.00277
900 MHz	0.00069
1400 MHz	0.00076
1800 MHz	0.00146
1900 MHz	0.00023
2100 MHz	0.00065
2300 MHz	0.00048
2600 MHz TDD	0.00044
2600 MHz FDD	0.00028
3.4 GHz	0.00239
3.8 GHz	0.00542
Others	0.16192
Total	0.21373

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.