

# **ICNIRP** Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	16/07/2025	Time Survey completed:	14:11
Survey address:	Prestwick KA9		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	57271744	26/03/2025
Probe	Agos Aria-6000 Antenna	1089	31/12/2023
Cabling	1.7m cable	1406	14/05/2025

<sup>&</sup>lt;sup>1</sup> https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

<sup>&</sup>lt;sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

### Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV


## Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

<sup>\*</sup> This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. \*\* All other frequencies between 30 MHz and 6 GHz.

### Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Measurement time:	13:20
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01151
174-230 MHz	0.01305
470-694 MHz	0.01137
700 MHz	0.00151
800 MHz	0.08854
900 MHz	0.09255
1400 MHz	0.00056
1800 MHz	0.00075
1900 MHz	0.00026
2100 MHz	0.00324
2300 MHz	0.00055
2600 MHz TDD	0.00043
2600 MHz FDD	0.00014
3.4 GHz	0.00155
3.8 GHz	0.00372
Others	0.15681
Total	0.38654

Measurement time:	13:38
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01194
174-230 MHz	0.01375
470-694 MHz	0.01182
700 MHz	0.00157
800 MHz	0.05624
900 MHz	0.01670
1400 MHz	0.00059
1800 MHz	0.00078
1900 MHz	0.00027
2100 MHz	0.02813
2300 MHz	0.00057
2600 MHz TDD	0.00044
2600 MHz FDD	0.00015
3.4 GHz	0.00163
3.8 GHz	0.00393
Others	0.16151
Total	0.31001

Measurement time:	13:46
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01185
174-230 MHz	0.01384
470-694 MHz	0.01182
700 MHz	0.00158
800 MHz	0.32446
900 MHz	0.11022
1400 MHz	0.00059
1800 MHz	0.00080
1900 MHz	0.00028
2100 MHz	0.03187
2300 MHz	0.00057
2600 MHz TDD	0.00044
2600 MHz FDD	0.00015
3.4 GHz	0.00165
3.8 GHz	0.00395
Others	0.16363
Total	0.67771

Measurement time:	13:54
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01184
174-230 MHz	0.01371
470-694 MHz	0.01183
700 MHz	0.00159
800 MHz	0.01570
900 MHz	0.01434
1400 MHz	0.00059
1800 MHz	0.00078
1900 MHz	0.00027
2100 MHz	0.01640
2300 MHz	0.00057
2600 MHz TDD	0.00044
2600 MHz FDD	0.00015
3.4 GHz	0.00165
3.8 GHz	0.00395
Others	0.16277
Total	0.25658

Measurement time:	14:05
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01182
174-230 MHz	0.01389
470-694 MHz	0.01184
700 MHz	0.00158
800 MHz	0.07652
900 MHz	0.09964
1400 MHz	0.00059
1800 MHz	0.00078
1900 MHz	0.00027
2100 MHz	0.00370
2300 MHz	0.00057
2600 MHz TDD	0.00044
2600 MHz FDD	0.00015
3.4 GHz	0.00165
3.8 GHz	0.00398
Others	0.16488
Total	0.39232

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.