

# **ICNIRP** Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	09/04/2025	Time Survey completed:	12:05
Survey address:	Manchester M7		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072599	11/02/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000	25/09/2023
Cabling	1.7m cable	1459	25/09/2023

<sup>&</sup>lt;sup>1</sup> https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

<sup>&</sup>lt;sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

### Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

## Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

<sup>\*</sup> This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. \*\* All other frequencies between 30 MHz and 6 GHz.

## Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Measurement time:	11:13
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01140
174-230 MHz	0.01178
470-694 MHz	0.00903
700 MHz	0.03112
800 MHz	0.00790
900 MHz	0.01144
1400 MHz	0.00266
1800 MHz	0.00305
1900 MHz	0.00021
2100 MHz	0.00708
2300 MHz	0.00043
2600 MHz TDD	0.00037
2600 MHz FDD	0.00125
3.4 GHz	0.00541
3.8 GHz	0.00538
Others	0.15800
Total	0.26651

Measurement time:	11:24
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01198
174-230 MHz	0.01238
470-694 MHz	0.00951
700 MHz	0.04558
800 MHz	0.00606
900 MHz	0.00245
1400 MHz	0.00124
1800 MHz	0.00206
1900 MHz	0.00022
2100 MHz	0.00188
2300 MHz	0.00048
2600 MHz TDD	0.00040
2600 MHz FDD	0.00047
3.4 GHz	0.00415
3.8 GHz	0.00578
Others	0.16832
Total	0.27296

Measurement time:	11:34
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01272
174-230 MHz	0.01275
470-694 MHz	0.00986
700 MHz	0.00946
800 MHz	0.00489
900 MHz	0.00322
1400 MHz	0.00169
1800 MHz	0.00265
1900 MHz	0.00023
2100 MHz	0.00352
2300 MHz	0.00048
2600 MHz TDD	0.00042
2600 MHz FDD	0.00030
3.4 GHz	0.00397
3.8 GHz	0.00608
Others	0.17494
Total	0.24718

Measurement time:	11:41
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01247
174-230 MHz	0.01296
470-694 MHz	0.00995
700 MHz	0.02555
800 MHz	0.00690
900 MHz	0.00476
1400 MHz	0.01386
1800 MHz	0.00770
1900 MHz	0.00024
2100 MHz	0.02017
2300 MHz	0.00048
2600 MHz TDD	0.00042
2600 MHz FDD	0.00055
3.4 GHz	0.00510
3.8 GHz	0.00617
Others	0.17864
Total	0.30594

Measurement time:	11:50
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01318
174-230 MHz	0.01325
470-694 MHz	0.01022
700 MHz	0.01342
800 MHz	0.00873
900 MHz	0.02166
1400 MHz	0.00179
1800 MHz	0.00275
1900 MHz	0.00024
2100 MHz	0.00320
2300 MHz	0.00051
2600 MHz TDD	0.00043
2600 MHz FDD	0.00035
3.4 GHz	0.00457
3.8 GHz	0.00638
Others	0.18233
Total	0.28302

Measurement time:	11:59
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01255
174-230 MHz	0.01363
470-694 MHz	0.01027
700 MHz	0.02361
800 MHz	0.01120
900 MHz	0.00633
1400 MHz	0.00310
1800 MHz	0.00249
1900 MHz	0.00024
2100 MHz	0.00619
2300 MHz	0.00050
2600 MHz TDD	0.00043
2600 MHz FDD	0.00126
3.4 GHz	0.01460
3.8 GHz	0.00653
Others	0.18415
Total	0.29708

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.