

## **ICNIRP** Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	01/05/2025	Time Survey completed:	15:46
Survey address:	Wolverhampton WV10		

Measureme	nt equipment	Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072603	13/02/2025
Probe	Agos Aria-6000 Antenna	ARIA6000-1158	25/09/2023
Cabling	1.7m cable	1458	18/01/2024

<sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

<sup>&</sup>lt;sup>1</sup> https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

# Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

<sup>\*</sup> This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. \*\* All other frequencies between 30 MHz and 6 GHz.

### Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Measurement time:	14:50
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00958
800 MHz	0.00707
900 MHz	0.00111
1400 MHz	0.00705
1800 MHz	0.00245
1900 MHz	0.00036
2100 MHz	0.00193
2300 MHz	0.00079
2600 MHz TDD	0.00071
2600 MHz FDD	0.00067
3.4 GHz	0.00396
3.8 GHz	0.00774
Others	0.12473
Total	0.16816

Measurement time:	15:01
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.02970
800 MHz	0.01278
900 MHz	0.00101
1400 MHz	0.01823
1800 MHz	0.01275
1900 MHz	0.00036
2100 MHz	0.00516
2300 MHz	0.00076
2600 MHz TDD	0.00071
2600 MHz FDD	0.00034
3.4 GHz	0.00469
3.8 GHz	0.00775
Others	0.12489
Total	0.21913

Measurement time:	15:11
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00308
800 MHz	0.00194
900 MHz	0.00101
1400 MHz	0.00112
1800 MHz	0.00129
1900 MHz	0.00036
2100 MHz	0.00111
2300 MHz	0.00078
2600 MHz TDD	0.00070
2600 MHz FDD	0.00032
3.4 GHz	0.00327
3.8 GHz	0.00751
Others	0.12158
Total	0.14406

Measurement time:	15:25
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00286
800 MHz	0.00740
900 MHz	0.00098
1400 MHz	0.00076
1800 MHz	0.00218
1900 MHz	0.00034
2100 MHz	0.00121
2300 MHz	0.00074
2600 MHz TDD	0.00067
2600 MHz FDD	0.00058
3.4 GHz	0.00314
3.8 GHz	0.00717
Others	0.11635
Total	0.14436

Measurement time:	15:40
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00838
800 MHz	0.00628
900 MHz	0.00109
1400 MHz	0.00418
1800 MHz	0.00300
1900 MHz	0.00033
2100 MHz	0.00256
2300 MHz	0.00072
2600 MHz TDD	0.00065
2600 MHz FDD	0.00071
3.4 GHz	0.00331
3.8 GHz	0.00689
Others	0.11258
Total	0.15069

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.